



Save as PDF



**0500 Transport Case**



Interior dimensions:  
88.7 x 46.8 x 64.1 cm (35" x 18" x 25")

- Watertight, crushproof, and dust proof
- Optional Pallet Riser Kit
- Optional Caster Wheel Kit complete with brakes
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Dual Integrated Automatic Pressure Equalization Valves
- Double wide grip fold down handles - makes lifting easy
- Peli Guarantee of Excellence
- Stainless steel hardware and padlock protectors
- Lid is completely removable
- Store documents outside the case with our Document Container
- Can be inverted and used as a pallet with an airtight cover



Black

**0500 Transport Case SPECIFICATIONS**

| Exterior Dimensions (L x W x D)             |                      | Interior Dimensions (L x W x D)            |  |
|---|----------------------|--|--|
| 101.4 x 59.5 x 72.7 cm<br>(40" x 23" x 29") |                      | 88.7 x 46.8 x 64.1 cm<br>(35" x 18" x 25") |  |
| Lid Depth                                   | Bottom Depth         | Total Depth                                |  |
| 5.7 cm<br>(2")                              | 58.4 cm<br>(23.00")  | 64.1 cm<br>(25.25")                        |  |
| Lid Depth                                   | Bottom Depth         | Total Depth                                |  |
| 5.7 cm<br>(2.25")                           | 58.4 cm<br>(23.00")  | 64.1 cm<br>(25.25")                        |  |
| Weight w/Foam                               | Weight w/o Foam      | Buoyancy Max.                              |  |
| 26.58 kg.<br>(58.6 lbs)                     | 22.68kg<br>(50 lbs.) | 353.8 kg<br>(780 lbs. )                    |  |
| Range Temperature                           |                      | No. of Wheels                              |  |
| -40 / 99° C<br>(-40 / 210° F)               |                      | 4 (Optional)                               |  |

**Materials**

| Body                   | Latch      | Lid O-Ring                            | Pins                   |
|------------------------|------------|---------------------------------------|------------------------|
| Polypropylene          | EXL        | PolymerStainless Steel                |                        |
| Foam                   | Purge Body | Purge Vent                            | Purge O-Ring           |
| 1.3 lb<br>Polyurethane | ABS        | 3 Micron<br>Hydrophobic Non-Woven PET | 70<br>Shore<br>Nitrile |

**Configuration**

| Cat. # | Description         |
|--------|---------------------|
| 0500   | 0500 Transport Case |

**0500 Transport Case Accessories**

| Cat. # | Description |
|--------|-------------|
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |
|        |             |