

ave as PDF



Peli protector cases - Computer protection - Laptop Overnight Case 1510LOC



Interior dimensions:

50.1 x 27.9 x 19.3 cm (20" x 11" x 8")

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Watertight, crushproof, and dust proof

Retractable extension handle

Strong polyurethane wheels with stainless steel bearings

Easy open Double Throw latches

Open cell core with solid wall design - strong, light weight

O-ring seal

Automatic Pressure Equalization Valve

Comfortable rubber over-moulded top and side handles

Stainless steel hardware and padlock protectors

Personalized nameplate service available

Unconditional Guarantee of Excellence

FAA maximum carry on size



Peli protector cases - Computer protection - Laptop Overnight Case 1510LOC SPECIFICATIONS

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)
55.9 x 35.1 x 22.9 cm	50.1 x 27.9 x 19.3 cm
(22" x 14" x 9")	(20" x 11" x 8")
Li	11

This case has internal wheel and/or handle wells that will reduce usable area. Please review for each application.

Lid Depth	Bottom Depth	Total Depth
4.5 cm	14.7 cm	19.2 cm
(2")	(5.79")	7.58")

Lid Depth	Bottom Depth	Total Depth
4.5 cm	14.7 cm	19.2 cm
(1.79")	(5.79")	7.58")

Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
6.17 kg.	5.44kg	29.1 kg	
(13.6 lbs)	(11.99 lbs.)	(64.15 lbs.)	

Range Temperature	No. of Wheels	Retractable Handle	
-40 / 99° C	2	Yes	
(-40 / 210° F)			

Personalized Nameplate Available

1510LOC Laptop Overnight Case Certificates

• IP67(1 meter submersion for 30 minutes)

Materials

Body	Latch	Lid O-Ring	Pi	ns
Polypropylene	ABS	PolymerStainless		
		Steel		

Foam	Purge Body	Purge Vent	Purge O- Ring
1.3 lb	ABS	3 Micron	70
Polyurethane	 	Hydrophobic Non-	Shore
		Woven PET	Nitrile

Configuration

Cat. #	Description
1510LOC	Peli protector cases - Computer protection -
	Laptop Overnight Case 1510LOC
	+

Peli protector cases - Computer protection - Laptop Overnight Case 1510LOC Accessories

No accessories are currently available for this product

• Def Stan 81-41/STANAG 4280