

CASES
1560M
Case

Save as PDF



1560M Case (Mobility Version)



Interior dimensions:
 51.7 x 39.2 x 22.9 cm (20" x 15" x 9")

Retractable extension handle

**10.2cm diameter x 3.8cm wide (4" x 1.5")
 heavy duty polyurethane wheels with stainless
 steel bearings**

Easy open Double Throw latches

Open cell core with solid wall design - strong, light weight

O-ring seal

Automatic Pressure Equalisation Valve

Comfortable rubber over-moulded top and side handles

Stainless steel hardware and padlock protectors

Personalized nameplate service available

Legendary Guarantee of Excellence

Water resistant, crushproof, and dust resistant

**1560M Case (Mobility Version)
 SPECIFICATIONS**

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
60.4 x 46.5 x 30.7 cm (24" x 18" x 12")		51.7 x 39.2 x 22.9 cm (20" x 15" x 9")	
Lid Depth	Bottom Depth	Total Depth	
5.1 cm (2")	17.8 cm (7.00")	22.9 cm (9.00")	
Lid Depth	Bottom Depth	Total Depth	
5.1 cm (2.00")	17.8 cm (7.00")	22.9 cm (9.00")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
0 kg. (lbs)	9.66kg (21.3 lbs.)	0 kg (lbs.)	
Range Temperature	No. of Wheels	Retractable Handle	
-40 / 99° C (-40 / 210° F)	2	Yes	

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	ABS	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O- Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non- Woven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1560M	1560M Case (Mobility Version)

**1560M Case (Mobility Version)
 Accessories**

No accessories are currently available for this product

Personalized Nameplate Available

**1560M Case (Mobility Version)
 Certificates**

- IP54