


MIL-STANDARD, SUBMERSIBLE, MULTI-FUNCTIONAL EQUIPMENT TRANSPORT SERIES

FEATURES INCLUDE:

- ultra high-strength polypropylene copolymer resin
- gasketed, water and dust-tight submersible design (MIL-C-4150J)
- resistent to UV, solvents, corrosion, fungus and impact damage (MIL-STD-810F)
- continuous molded-in hinge with stainless steel pin
- patent pending "trigger release" latch system
- comfortable, snap-down, rubber over-molded handle
- automatic ambient pressure equalization valve (MIL-STD-648C and IP67)
- cases stack securely and accommodate padlocks

SUGGESTED APPLICATIONS

- camera, video and portable GPS gear
- music recording and playback equipment
- satellite phones and radios
- police and military gear
- boat gear, fishing reels
- fire, rescue and first aid equipment
- portable electronics



- * BUILT IN TSA TRIGGER LATCHES STANDARD

 ** ACCEPTS TSA TRIGGER LATCHES AVAILABLE SEPARETLY

INTERIORS

E-Empty

- C Cubed Foam
- L Layered Foam D- Padded Dividers
- N Laptop Interior

Product Code Breakdown





- INT. Length / Width INT. Total Depth
- COLOR (black)
- INTERIOR (cubed foam)



3I-2015-10B





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!


MIL-STANDARD UTILITY CASE



FEATURES INCLUDE:

- Superior rotationally molded strength and ergonomic design.
- Impenetrable, yet lightweight LLDPE shell for maximum impact resistence.
- UV, solvent, corrosion and fungus resistant (MIL-STD-810F).
- Complete gasket seal makes these cases absolutely watertight (MIL-C-4150J).
- Automatic ambient pressure equalization valve (MIL-STD-648C & IP67).
- Black powder coated stainless steel hardware prevents rusting.
- Comfortable, spring-loaded, rubber over-molded handles.
- These cases are designed and built to withstand levels of punishment in excess of all ATA and most industrial and military shipping specifications.

| | | I | | CASTERS AND FOAM INSERT OPTIONS | | | | |
|----------------|---------------------------|--------------|---------|---------------------------------|-----------------|--------------------|---------------|-----------------|
| Part # | Inside L X W X H | LID depth | | handle and wheels | caster kit * | padded dividers | cubed foam | layered foam |
| 3R1919-14B | 19" x 19" x 14-1/2" | 3" | 11 3/8" | х | | | х | |
| 3R2216-15B-E | 22" x 16" x 15" | 3" | 12" | | | | | |
| 3R2217-10B | 22" x 17" x 10-1/2" | 3" | 7-1/2" | Х | | х | х | |
| 3R2222-12B | 22" x 22" x 12" | 3" | 9" | Х | | х | х | |
| 3R2222-20B | 22" x 22" x 20" | 3-1/2" | 16-1/2" | | х | | х | |
| 3R2423-17B | 24" x 23" x 17" | 3-1/2" | 13-1/2" | Х | | | х | |
| 3R2424-24B | 24" x 24" x 24" | 3-1/2" | 20-1/2" | | х | | | х |
| 3R2727-18B | 27" x 27" x 18" | 3-1/2" | 14-1/2" | | х | | | х |
| 3R2727-27B | 27" x 27" x 27" | 3-1/2" | 23-1/2" | | Х | | | х |
| 3R2817-10B*** | 28-3/4"x 17-1/2"x 10-5/8" | 2" | 8-5/8" | Х | | | Х | |
| 3R3025-15B | 30" x 25" x 15" | 3-1/2" | 11-1/2" | Х | | | х | |
| 3R3214-15B | 32" x 14-1/2" x 15-3/4" | 3-1/4" | 12-1/2" | Х | | | Х | |
| 3R4024-18B | 40" x 24" x 18" | 3-1/2" | 14-1/2" | | Х | | | х |
| 3R4024-24B | 40" x 24" x 24" | 3-1/2" | 20-1/2" | | Х | | | х |
| 3R4417-8B-EW** | 44-1/4" x 17-1/2" x 8" | 3-1/8" | 4-7/8" | Х | | | | |
| 3R4530-24B-E | 45" x 30" x 24" | 3-1/2" | 20-1/2" | | Х | | | |
| 3R4909-5B-E** | 49-1/2" x 9" x 5-1/2" | 2-1/4" | 3-1/4" | | | | | |
| 3R5030-24B-E | 50" x 30" x 24" | 3-1/2" | 20-1/2" | | Х | | | |
| 3R5212-7B-EW** | 52-1/2" x 12-1/8" x 8" | 3-1/8" | 4-7/8" | Х | | | | |



** BUILT-IN TSA TRIGGER LATCHES STANDARD; ALSO OFFERED AS 2R SERIES CASES IN BLACK, OLIVE DRAB OR TAN WITH CONVOLUTED FOAM INSERTS.

*** BUILT-IN TSA TRIGGER LATCHES STANDARD

3R 2217-10B

■ ROTO SERIES ■ INT. Length / Width ■ INT. Total Depth ■ COLOR (black)







SKB's new Rolling Roto Shock Racks feature a (20" deep) roto molded tough shell with an integrally molded valance that eliminates the need for a metal valance on the outside of the case.

FEATURES INCLUDE:

Standard 19" rack width per EIA standards

■ Rack depth front to rear rail is 20" and each lid is 2-1/4" deep

 Threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration

 Recessed TSA trigger release latches allow for opening while stacked

 Secure stacking design allows full use of doors while racks are stacked together

 8 elastomeric shocks with a load range of from 40 lbs. to 150 lbs.)

· Load range may be increased up to 300 lbs. with optional additional HM-245 elastomeric shocks (see website for details)

- Gasket sealed front and rear doors
- Ambient pressure relief valve
- Sliding retractable handle
- Oversized snap-down handles on each side of the case
- Convenient roller blade wheels
- Cases stocked in Black
- Custom colors available (minimum quantities apply)

Standard dimensions front to rear rail: 20"

| | Part # | Rack Units | Height | Lid Depth |
|---|--------------|------------|---------|-----------|
| | 3SKB-R04U20W | 4 space | 7" | 2-1/4" |
| | 3SKB-R06U20W | 6 space | 10-1/2" | 2-1/4" |
| ſ | 35KB-R08U20W | 8 space | 14" | 3-1/4" |
| • | 3SKB-R10U20W | 10 space | 17-1/2" | 3-1/4" |
| • | 3SKB-R12U20W | 12 space | 21" | 3-1/4" |

* - Available Summer 2008







relief valves

SPORTS PRODUCTS 800.654.5992

INDUSTRIAL PRODUCTS 800.783.0087

www.skbcases.com





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!


20" RACK CASES WITH ELASTOMER SHOCKS



SKB's new Roto Shock Racks feature a (20" deep) roto molded tough shell with an integrally molded valance that eliminates the need for a metal valance on the outside of the case.

FEATURES INCLUDE:

- Standard 19" rack width per EIA standards.
- Redesigned frame with threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration.
- Standard rack depth front to rear rail is 20".
- Front and rear doors are fitted with rubber gaskets for water resistant protection.





www.skbcases.com

Molded-in handles and secure stackability.

AVAILABLE SIZES :

All Standard depths - front to rear rail: 20"

| Part # | Lid Depth | Rack Units | Height |
|--------------|-----------|------------|--------------|
| 1SKB-R904U20 | 2-1/4" | 4 space | 7" High |
| 1SKB-R906U20 | 2-1/4" | 6 space | 10-1/2" High |
| 1SKB-R908U20 | 3-1/4" | 8 space | 14" High |
| 1SKB-R910U20 | 3-1/4" | 10 space | 17-1/2" High |
| 1SKB-R912U20 | 3-1/4" | 12 space | 21" High |
| 1SKB-R914U20 | 3-1/4" | 14 space | 24-1/2" High |
| 1SKB-R916U20 | 3-1/4" | 16 space | 28" High |
| 1SKB-1916 | | Caster Ca | rt |

- Come standard with 8 each HM-245 elastomeric, high damping, wide temperature range shock mounts with a load range of 40 to 150 lbs.
- Additional or stiffer shock mounts may be ordered from the factory and are easily field-installed (call for details & availability).
 - NOTE: *These sizes are not designed to accept additional elastomer shock absorbers.
- Easy-grip molded handles.
- Molded-in lugs allow all sizes within the series as well as the caster cart to stack securely.



FEATURES INCLUDE:

Standard dimensions - front to rear rail: 24"

■ Standard 19" rack width per EIA standards.

Standard rack depth front to rear rail is 24" and each lid is 4.5" deep.

 Redesigned frame with threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration.


■ Unique "plug" style lid sealing system. Lids penetrate the body with an approximate 1" molded-in protrusion that provides outstanding sealing and anti-shear properties.

Patent-pending compound hinge system allows the lids to swing out 270° and rest along the sides of the case or easily removed and reinstalled in seconds.

• Front and rear doors are fitted with rubber gaskets for water resistant protection.

 Recessed heavy-duty twist latches allow these cases to meet most ATA and military specifications.

- Stacks securely with wheels on or off and this revolutionary design also allows for both lids to open completely while cases are stacked.
- All sizes come standard with 8 each HM-245 elastomeric, high damping, wide temperature range shock mounts with a load range of 40 to 150 lbs.
- Additional or stiffer shock mounts may be ordered from the factory and are easily fieldinstalled (call for details & availability).
- Standard high quality slide-in/out locking swivel 4" casters rated at 1,200 lbs.
- Automatic ambient pressure equalization valve (MIL-STD-648C)
- Black powder coated stainless steel key-lockable latches.
- Comfortable, spring-loaded, rubber over-molded handles.



SKB Compound hinge technology allows 270 door swing range even when cases are in a stacked position





3SKB-R916U24

MUSIC PRODUCTS 800.410.2024 SPORTS PRODUCTS 800.654.5992 **INDUSTRIAL PRODUCTS 800.783.0087** www.skbcases.com



- Standard 19" rack width per EIA standards.
- Standard rack depth front to rear rail is 29 1/4" and each lid is 4 1/2" deep.
- Standard with square rackmounting holes for cage nuts (not included)
 and aluminum cross components forming an "H" shaped rigid configuration.
- Easily adaptable to 10-32 tapped or 5/32" round (0.183") through holes.
- Unique "plug" style lid sealing system. Lids penetrate the body with an approximate 1" molded-in protrusion that provides outstanding sealing and anti-shear properties.
- Patent-pending compound hinge system allows the lids to swing out 270°
 and rest along the sides of the case or be easily removed and reinstalled in seconds.
- Front and rear doors are fitted with rubber gaskets for water resistant protection.
- Recessed heavy-duty twist latches allow these cases to meet most ATA and military specifications.
- Stacks securely with wheels on or off and this revolutionary design also allows for both lids to open completely while cases are stacked.
- All sizes come standard with 8 each HM-245 elastomeric, high damping, wide temperature range shock mounts with a load range of 40 to 150 lbs.
- Additional or stiffer shock mounts may be ordered from the factory and are easily field-installed.
- Standard high quality slide-in/out locking swivel 4" casters rated at 1,200 lbs.
- Automatic ambient pressure equalization valve (MIL-STD-648C).
- Black powder coated stainless steel key-lockable latches.
- Comfortable, spring-loaded, rubber over-molded handles.



Patent Pending





Standard dimensions front to rear rail: 29 1/4"

Height

10-1/2

17-1/2

14"

Lid Depth

4-1/2"

4-1/2"

4-1/2

Rack Units

4 space

6 space

8 space

10 space

Part #


3SKB-R904U28

3SKB-R906U28

3SKB-R908U28

3SKB-R910U28





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE

30" RACK CASES
WITH
ELASTOMER
SHOCKS



Slide Mount Casters with 'spring-out' Position Stops

SKB's new Roto Shock Racks feature a (30" deep) roto molded tough shell with an integrally molded valance that eliminates the need for a metal valance on the outside of the case.

FEATURES INCLUDE:

Standard 19" rack width per EIA standards.

Standard rack depth front to rear rail is 30" and each lid is 4.5" deep.

Redesigned frame with threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration.

• Unique "plug" style lid sealing system. Lids penetrate the body with an approximate 1" molded-in protrusion that provides outstanding sealing and anti-shear properties.

Patent-pending compound hinge system allows the lids to swing out 270°
 and rest along the sides of the case or easily removed and reinstalled in seconds.


• Front and rear doors are fitted with rubber gaskets for water resistant protection.

 Recessed heavy-duty twist latches allow these cases to meet most ATA and military specifications.

Stacks securely with wheels on or off and this revolutionary design also allows for both lids to open completely while cases are stacked.

All sizes come standard with 8 each HM-245 elastomeric, high damping, wide temperature range shock mounts with a load range of 40 to 150 lbs.

- Additional or stiffer shock mounts may be ordered from the factory and are easily fieldinstalled (call for details & availability).
- Standard high quality slide-in/out locking swivel 4" casters rated at 1,200 lbs.
- Automatic ambient pressure equalization valve (MIL-STD-648C)
- Black powder coated stainless steel key-lockable latches.
- Comfortable, spring-loaded, rubber over-molded handles.



SKB Compound hinge technology allows 270° door swing range even when cases are in a stacked position.



Both lids can be impletely removed and re-attached imply and quickly.



elastomers

Standard dimensions front to rear rail: 30"



relief valves

MUSIC PRODUCTS 800.410.2024 SPORTS PRODUCTS 800.654.5992 INDUSTRIAL PRODUCTS 800.783.0087

www.skbcases.com

3SKB-R906U30



19" ULTIMATE STRENGTH STACKING RACKMOUNT SYSTEM



AVAILABLE SIZES:

1SKB-R4

1SKB-R6

1SKB-R8

1SKB-R10

1SKB-R12

Rack Units

4 space

6 space

8 space

10 space

12 space

1SKB-R8 - 8 space rack

pictured with both front

and rear lids removed.

Height

7" High

21" High

10-1/2" High 14" High

17-1/2" High

"Million Mile Warranty"

YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!

SKB ROTO MOLDED 19" RACKS

FEATURES INCLUDE:

- roto molded tuff shell
- recessed heavy-duty twist latches
- molded-in unbendable valance
- solid stackability
- steel threaded front rails are factory installed
- rear rails can be customer installed at any time
- all rails are replaceable kits sold separately

SUGGESTED APPLICATIONS:

- rackable mixers and amplifiers
- recording and playback equipment
- rackable pullout drawers and shelves ref- 1SKB-DRWR-4 and 1SKB-VS1



Easily installed rear rail kits are available for all US Racks: 1SKB-RRK4, RRK6, RRK8, RRK10, RRK12 1SKB-1904 Caster Kit is also available.



SPORTS PRODUCTS 800.654.5992 INDUSTRIAL PRODUCTS 800.783.0087







YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!

SHIPPING CONTAINERS

available in over



recesses for mounting except the 3SKB-X4530-24 which includes casters as standard equipment.

*These Roto-X sizes do not have Note: all measurements are interior dimensions. Tolerance± .25"

ROTO-X FEATURES INCLUDE:

- · Rotationally molded for maximum strength and impact resistance.
- Stack securely for efficient transport and storage.
- Spring loaded 90° lifting handles.
- Available heavy-duty removable, lockable swivel caster kits.
- Heavy-duty twist latches will accommodate padlocks.

SUGGESTED APPLICATIONS:

- Heavy equipment transport.
- Machine parts and military gear.
- Boat gear, fishing equipment.
- Fire, rescue and first aid equipment.

| | Casters as standard e | quipment. unnensions. i | Olerance1.25 |
|--------------|-----------------------|---------------------------|----------------|
| Part number | Description | LxWxH | lid / base |
| *3SKB-X1814 | 12 TOOL CASE | 18"X14"X12" | 3"/9" |
| *3SKB-X1818 | 10 TOOL CASE | 18"X18"X10" | 5"/5" |
| *3SKB-X1818 | | 18"X18"X14" | 4-1/2"/ 9-1/2" |
| *3SKB-X1818 | 18 SQUARE | 18"X18"X18" | 4"/14" |
| 3SKB-X2318 | 16 FT LOCKER | 23"X18"X16" | 3"/13" |
| 3SKB-X2415 | 10 TOOL CASE | 24"X15"X10-1/2" | 5-1/4"/5-1/4" |
| 3SKB-X2424 | 14 SQUARE | 24"X24"X14" | 3"/11" |
| 3SKB-X2424 | 18 SQUARE | 24"X24"X18" | 3"/15" |
| 3SKB-X2424 | 22 SQUARE | 24"X24"X22" | 7"/15" |
| 3SKB-X2513 | 16 FT LOCKER | 25-1/4"X12-3/4"X16" | 4"/12" |
| 3SKB-X2624 | 32 FT LOCKER | 26"X24"X32" | 12"/ 20" |
| 3SKB-X2719- | 10 TOOL CASE | 27"X19"X10" | 5"/5" |
| 3SKB-X2828- | 22 SQUARE | 28"X28"X22" | 8"/14" |
| 3SKB-X2915 | -14 FT LOCKER | 29"X15"X14" | 3"/11" |
| 3SKB-X3226 | 30 FT LOCKER | 32"X26"X30" | 8"/22" |
| 3SKB-X3426- | 16 FT LOCKER | 34"X26"X16" | 3"/13" |
| 3SKB-X3518 | 15 FT LOCKER | 35"X18"X15" | 5"/10" |
| 3SKB-X3722- | 21 FT LOCKER | 37-1/4"X21-3/4"X21 3/4" | 6-1/2"/ 15-1/4 |
| * 3SKB-X4530 | 24 FT LOCKER | 43-1/4" x28-1/4" x21-3/4" | 3-1/4"/18-1/2 |
| 3SKB-X5026- | 16 FT LOCKER | 50"X26"X16" | 3"/13" |
| 3SKB-X5030- | 24 FT LOCKER | 50"X30"X24" | 4"/20" |
| 3SKB-CAST | CASTER KIT | set of 4 | |





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!



TRANSPORT CONTAINERS
WITH RETRACTABLE HANDLES
AND WHEELS




telescoping style handle pictured here is used on these case sizes.

metal,

FEATURES INCLUDE:

- Case shells are molded of durable, impact resistent high density polyethylene.
- · Convenient retractable pull-handle.
- Quiet, durable roller-blade style wheels.
- Molded-in protective bumpers protect hardware.
- Heavy-duty latch system
- Comfortable, spring loaded side handles.

Now available in 14 stock sizes.










YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!

MILITARY STYLE SHIPPING CONTAINERS





MAXIMUM PROTECTION CASES Military-style shipping containers.

AVAILABLE IN SEVEN SIZES

| Dimensions | lxwxh | Lid | Base |
|------------|-----------------------------|--------|--------|
| 3SKB-1212M | 12" x 12" x 8" | 3-3/4" | 4-1/4 |
| 3SKB-1616M | 16" x 16" x 13" | 5" | 8" |
| 3SKB-1814M | 18" x 14-7/8" x 9-1/2" | 4-1/2" | 5" |
| 3SKB-2218M | 22" x 18" x 9-5/8" | 5" | 4-5/8" |
| 3SKB-2421M | 24" x 21" x 9" | 4" | 5" |
| 3SKB-2825M | 27-3/4" x 25-3/4" x 18" | 9" | 9" |
| 3SKB-3018M | 30-1/4" x 19-1/4" x 17-1/2" | 8" | 9-1/2" |

FEATURES INCLUDE:

- gasketed, heavy-duty "L" valance insures secure closure
- resistent to UV, solvents, corrosion, fungus and impact damage.
- molded-in protective bumpers
- heavy-duty twist latch system
- comfortable, spring loaded side handles
- cases stack securely and accommodate padlocks

Custom Colors available on special order





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE !

LUGGAGE-STYLE CARRYING CASES WITH HORIZONTAL RIB DESIGN

dimensions lxw

case number

lid depth

base depth

This SKB line of heavy-duty parallel rib cases offers sleek, contemporary styling, consistently fine craftsmanship and unequaled durability. Ultra High Molecular Weight Polyethylene, resistant to oils, fuels, solvents and acids can withstand temperatures from -80 F to 185F and provides maximum impact strength.





service representatives with any questions.

NOTES: All measurements reflect interior dimensions. Dimensional tolerance on "LS Series" cases is .25"



| IN-9 I OCK 912 | ES - AVAILABLE FOR | EXPEDIENT | DELIVERY |
|----------------|------------------------------------|------------------|-----------|
| 9P1108-01 | 11-1/4" x 8-3/8" | 2" | 3" |
| 9P1410-01 | 14-3/8" x 10-3/8" | 2-1/2" | 3-1/2" |
| 9P1410-02 | 14-3/8" x 10-3/8" | 3" | 9" |
| 9P1712-01 | 17-3/8" x 12-3/8" | 2" | 2-1/2" |
| 9P1712-02 | 17-3/8" x 12-3/8" | 2 1/2" | 3-1/2" |
| 9P1912-01 | 19" x 12-3/8" | 2-1/2" | 3" |
| 9P2012-01 | 20-3/8" x 12-3/8" | 2-3/4" | 3-3/4" |
| 9P2014-01 | 20-3/8" x 14" | 3" | 4" |
| 9P2016-01 | 20-3/8" x 16-3/8" | 3" | 4-1/2" |
| 9P2218-01 | 22" x 18" | 3-1/2" | 4-1/2" |
| 9P2517-01 | 25-3/8" x 17-3/8" | 4-1/4" | 4-3/4" |
| 9P2520-01 | 25-5/8" x 20-3/4" | 4-1/4" | 4-3/4" |
| CHISTOM SIZES | - MINIMUM QUANTITIES | ADDIV - CALI | EOR QUOTE |
| | 11-1/4" x 8-3/8" | 4-1/2" | |
| 1108P | 11-1/4 x 8-3/6 11-1/2" x 8-1/2" | | 2" |
| 1108N | 11-1/2 x 6-1/2 | 6-1/4" | |
| 1209N | 11-7/8" x 11-7/8" | 4-1/4" | 2" |
| 1212N | 13-1/4" x 7-1/4" | 4-1/2" 3" | 2" |
| 1307N | 13-3/8" x 8-1/8" | 6" | 2" |
| 1308N 1309N | 13-3/8" x 9-7/8" | 7" | 2" |
| 1309N 1409N | 13-3/6 X 9-7/6 14-1/2" x 9" | | 2" |
| 1409N 1410P | 14-1/2 x 9 14-3/8" x 10-3/8" | 4-1/4" 9-1/2" | 2" |
| | 14" x 13-3/8" | 6" | 2" |
| 1413N 1511N | 14 X 13-3/8 14-5/8" x 10-5/8" | 1-12" | 1-1/2" |
| 1610N | 16-1/4" x 10" | 3" | 1-1/2" |
| 1611P | 16-1/4" x 11" | 4-1/2" | 2" |
| 1611N | 16-1/4" x 11-3/8" | 3" | 1-1/2" |
| 1613P | 16-5/8" x 13-3/8" | 4-1/2" | 2" |
| 1712P | 17-3/8" x 12-3/8" | 4-1/2" | 2" |
| 1712P 1809N | 18" x 9" | 6" | 2" |
| 1909N | 19-1/8" x 9-1/8" | 6" | 2" |
| 1912P | 19" x 12-3/8" | 4-1/2" | 2" |
| 1913N | 19-1/4" x 13-7/8" | 5" | 2" |
| 1914P | 19-3/8" x 13-3/4" | 6" | 2" |
| 1915N | 19-3/8" x 15" | 7" | 2" |
| 2010N | 20-1/2" x 10 | 11" | 2" |
| 2011P | 20-3/4" x 11-1/2" | 4-1/2" | 2" |
| 2011N | 20-5/8" x 11-5/8" | 5" | 2" |
| 2012P | 20-3/8" x 12-3/8" | 4-1/2" | 2" |
| 2013N | 20-1/4" x 13-3/4" | 3-1/2" | 2" |
| 2014P | 20-3/8" x 14" | 4-1/2" | 2" |
| 2016P | 20-3/8" x 16-3/8" | 4-1/2" | 2" |
| 2115P | 21-1/2" x 15-3/8" | 4-1/2" | 2" |
| 2214N | 22-1/4" x 14 | 3-1/2" | 2" |
| 2218P | 22" x 18 | 4-1/2" | 2" |
| 2314P | 23-1/2" x 14-3/4" | 5" | 2" |
| 2407N | 23-3/4" x 7" | 6" | 2" |
| 2419N | 24-1/4" x 19-1/4" | 3-1/2" | 1-1/2" |
| 2516P | 25" x 16-1/2" | 5-1/2" | 2" |
| 2517P | 25-3/8" x 17-3/8" | 4-3/4" | 2" |
| 2520P | 25-5/8" x 20-3/4" | 4-3/4" | 2" |
| 2714N | 27" x 14" | 2-1/2" | 2" |
| 2717N | 27-3/4" x 17-/4" | 9-1/2" | 2" |
| 2906N | 29-3/4" x 6-3/4" | 4-1/2" | 2" |
| 2912N | 28-3/4" x 11-3/4" | 4-1/2" | 2" |
| 3121N | 31-1/4" x 21-1/2" | 7-1/2" | 2" |
| 3515S | 35-1/8" x 15-1/4" | 5-1/4" | 2" |
| 3618P | 36-1/2" x 18-1/2" | 7-1/2" | 2" |
| 3725N | 37" x 25" | 9-1/4" | 2" |
| 4209N | 42-3/8" x 9-1/4" | 5" | 2" |
| 5017P | 50-3/8" x 17-3/8" | 7-1/2" | 2" |
| 7210S | 72-3/8" x 10" | 3" | 2" |
| 7219S | 72-3/8" x 19-1/4" | 3" | 2" |



YOU BREAK IT...WE REPLACE IT, FOR FREE, FOR LIFE!



LOW PROFILE ATA TRANSPORT CASES WITH WHEELS

- Heavy duty built-in wheels and durable spring-loaded end handles deliver effortless mobility.
- Prominent bumpers protect gasketed aluminum valance at every critical impact point.


| | Dimensions lxwxh | Lid | Base |
|------------|------------------------|--------|--------|
| 3SKB-4212W | 42" x 11-3/4" x 6" | 3" | 3" |
| 3SKB-4316W | 43-1/2" x 16" x 6" | 3" | 3" |
| 3SKB-5211W | 52" x 11-3/4" x 6" | 3" | 3" |
| 3SKB-5216W | 52-1/4" x 16-1/2" x 6" | 3" | 3" |
| 3SKB-6019W | 60-1/4" x 19-1/4" x 6" | 3" | 3" |
| 3SKB-6022W | 60-1/4" x 22-1/4" x 6" | 3" | 3" |
| 3SKB-6323W | 63" x 23" x 10-1/4" | 5-1/8" | 5-1/8" |



UNIVERSAL LOW PROFILE CASES W/VELCRO LINER AND 4 PATENTED RE-POSITIONABLE CORNERS

| | Dimensions l x w x h | Lid | Base |
|-----------|------------------------|--------|--------|
| 1SKB-3026 | 29" x 26" x 8 1/2" | 4" | 4-1/4" |
| 1SKB-3423 | 34-1/2" x 22-3/4" x 9" | 5-1/2" | 3-1/2" |
| 1SKB-4031 | 40" x 31" x 9-1/2" | 4-3/4" | 4-3/4" |







RAIL-PACK UTILITY CASES

| | Dimensions | lxwxh |
|-------------|----------------|-----------------|
| 1SKB-H3611W | 36-3/4" X 12" | X 8-1/4" |
| 1SKB-H4810W | 47-1/8" X 9-7/ | 8" X 9-3/8" |
| 1SKB-H4812W | 48-1/8" X 11-1 | L/4" X 11"5" 6' |
| 1SKB-H4816W | 48-1/4" X 16" | X 12-3/8" |
| 1SKB-H5020W | 49-3/4"X 20" X | X 13-3/4" |





YOU BREAK IT. . . WE REPLACE IT, FOR FREE, FOR LIFE!

ROTO MOLDED LCD SCREEN CASES



3SKB-3237
32" to 37" Screens includes one over-molded tow handle on each end and two over-molded lifting handles on each side





The 3SKB-2026 LCD Screen Case and 3SKB-3237 LCD Screen Case are rotationally molded of LLDPE Polyethylene for strength and durability. The interiors are designed to hold LCD screens in the desirable upright position with a universal interior foam padding system designed to configure easily for customized protection. SKB LCD Screen Cases offers superb quality and construction and are guaranteed for life.

FEATURES INCLUDE:

- Holds LCD screens in desirable upright position
- Universal 2" thick foam padding system for easy configuration
- (4) Convoluted foam pieces for side to side protection
- (2) Adjustable convoluted foam pieces for perfect fit top to bottom
- · Corner wheels for tilting and easy transport
- Rotationally molded of LLDPE Polyethylene for strength and durability
- Comfortable and durable rubber over-molded handles
- Weather resistant gasketed tongue and groove valance for moisture protection
- Heavy duty twist latches with one padlockable latch on each side
- Can be shipped standard UPS or Fed X

Cases will hold screens with stands for most models on the market.





