



Save as PDF



1460 Case



Interior dimensions:
47.1 x 25.2 x 27.7 cm (19" x 10" x 11")

Top lid opens up to 180° for on-the-field anti-roll stability when open

- Easy open Double Throw latches
 - Open cell core with solid wall design - strong, light weight
 - O-ring seal
 - Automatic Pressure Equalisation Valve
 - Comfortable rubber over-moulded handles
 - Stainless steel hardware and padlock protectors
 - Pick N Pluck™ foam
 - Personalised nameplate service available
 - Unconditional Guarantee of Excellence
 - Also available with EMS Organiser and Dividers
 - Watertight, crushproof, and dust proof
- Watertight, crushproof, and dust proof**



Black Desert tan Green

1460 Case SPECIFICATIONS

Exterior Dimensions (L x W x D)			Interior Dimensions (L x W x D)		
52.9 x 32.3 x 32.4 cm (21" x 13" x 13")			47.1 x 25.2 x 27.7 cm (19" x 10" x 11")		
Lid Depth	Bottom Depth	Total Depth			
12.5 cm (5")	15.3 cm (6.01")	27.7 cm (10.92")			
Lid Depth	Bottom Depth	Total Depth			
12.5 cm (4.91")	15.3 cm (6.01")	27.7 cm (10.92")			
Weight w/Foam	Weight w/o Foam	Buoyancy Max.			
5.66 kg. (12.48 lbs)	3.97kg (8.75 lbs.)	37.19 kg (82 lbs.)			
Range Temperature					
-40 / 99° C (-40 / 210° F)					

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	EXL	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
Polyurethane 6 pieces	ABS	3 Micron Hydrophobic Nonwoven PET	70 Shore Nitrile

Configuration

Cat. #	Description
1460	1460 Case

1460 Case Accessories

Cat. #	Description

1460 Case Certificates

- IP67(1 meter submersion for 30 minutes)