

Uncontrolled document as of March 24, 2014. Refer to website for up to date specifications.



Save as PDF



Peli protector cases - Protector cases - 1730 Transport Case



Interior dimensions:

86.3 x 60.9 x 31.7 cm (34" x 24" x 13")

- Watertight, crushproof, and dust proof
- Easy open Double Step latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Optional Humidity gauge changes color above 40%
- Fold down handles
- Strong polyurethane wheels with stainless steel bearings
- Stainless steel hardware and padlock protectors
- 5-piece foam set
- Personalized nameplate service available
- Unconditional Guarantee of Excellence
- Extra-deep base-to-lid, locking cleats



Black Desert_tanOd_green

Peli protector cases - Protector cases - 1730 Transport Case SPECIFICATIONS

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
95.2 x 68.9 x 36.5 cm (38" x 27" x 14")		86.3 x 60.9 x 31.7 cm (34" x 24" x 13")	
Lid Depth	Bottom Depth	Total Depth	
6.3 cm (3")	25.4 cm (10.00")	31.7 cm (12.50")	
Lid Depth	Bottom Depth	Total Depth	
6.3 cm (2.50")	25.4 cm (10.00")	31.7 cm (12.50")	
Weight w/Foam	Weight w/o Foam	Buoyancy Max.	
17.24 kg. (38 lbs)	13.61kg (30 lbs.)	188.69 kg (416 lbs.)	
Range Temperature		No. of Wheels	
-40 / 99° C (-40 / 210° F)		2	

Personalized Nameplate Available

1730 Transport Case Certificates

- IP67(1 meter submersion for 30 minutes)

Materials

Body	Latch	Lid O-Ring	Pins
Polypropylene	ABS	PolymerStainless Steel	
Foam	Purge Body	Purge Vent	Purge O-Ring
1.3 lb Polyurethane	ABS	3 Micron Hydrophobic Non- Woven	70 Shore Nitrile

Configuration

Cat. #	Description
1730	Peli protector cases - Protector cases - 1730 Transport Case

Peli protector cases - Protector cases - 1730 Transport Case Accessories

Cat. #	Description