

# Polyolefin

- Shrink Temp. 194°F
- Flame Retardant
- Versatile & Economical Termination Solution
- Wide Selection of Sizes and Colors
- Resists Common Automotive Chemicals
- Easily Installs Over Connectors & Splices
- Mil-I-23053/5

Shrinkflex heatshrink tubing is the ideal way to create a tight, professional finish on any wire, hose or cable management project.

## 2:1 Polyolefin Heatshrink Tubing

When economy is the driving force, 2:1 Shrinkflex heatshrink tubing is the answer. Not as versatile as a high ratio shrink product, 2:1 will still slide easily over small inline splices and connectors and provide a tight seal in many applications.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
3/64"	H2N0.05	1.3mm	0.6mm	500'	25'	11	0.16
1/16"	H2N0.06	1.8mm	0.8mm	500'	25'	11	0.22
1/8"	H2N0.13	3.4mm	1.6mm	500'	25'	11	0.43
3/16"	H2N0.19	5.0mm	2.4mm	500'	25'	BK & CL	0.60
1/4"	H2N0.25	6.4mm	3.2mm	250'	25'	11	1.04
3/8"	H2N0.38	9.5mm	4.8mm	200'	25'	11	1.31
1/2"	H2N0.50	12.7mm	6.4mm	200'	25'	11	1.52
5/8"	H2N0.63	16.7mm	8.0mm	100'	25'	11	2.12
3/4"	H2N0.75	19.1mm	9.4mm	100'	25'	11	2.58
1"	H2N1.00	25.7mm	12.7mm	100'	25'	11	3.74
1 1/2"	H2N1.50	38.1mm	19.1mm	100'	25'	11	5.53
2"	H2N2.00	51.0mm	25.4mm	100'	25'	11	8.25
3"	H2N3.00	76.2mm	38.1mm	100'	25'	BK,CL,GN,GY,RD,WH,YL	13.15
4"	H2N4.00BK	101.6mm	50.8mm	100'	25'	BK	23.50



Shrinkflex works great for color coding and wire harnessing applications.

## 3:1 Polyolefin Heatshrink Tubing

The high shrink ratio of 3:1 Shrinkflex heatshrink tubing ensures that the tubing will slip over large connectors or plugs and still provide a tight, professional seal.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/16"	H3N0.06	1.5mm	0.5mm	500'	25'	11	0.18
1/8"	H3N0.13	3.0mm	1.0mm	500'	25'	11	0.37
3/16"	H3N0.19	4.5mm	1.5mm	250'	25'	11	0.55
1/4"	H3N0.25	6.0mm	2.0mm	250'	25'	11	0.74
3/8"	H3N0.38	9.0mm	3.0mm	200'	25'	11	1.01
1/2"	H3N0.50	12.0mm	4.0mm	200'	25'	11	1.28
3/4"	H3N0.75	18.8mm	6.0mm	100'	25'	11	1.87
1"	H3N1.00	24.0mm	8.0mm	100'	25'	11	2.86
1 1/2"	H3N1.50	38.0mm	13.0mm	100'	25'	11	4.51
2"	H3N2.00	50.0mm	17.0mm	100'	25'	11	6.33
3"	H3N3.00	75.0mm	25.4mm	100'	20'	BK	10.33



Convenient packaging.

